

# TECHNICAL DATA SHEET



## ALL PURPOSE HEAVY DUTY DEGREASER PROFESSIONAL GRADE

### INDUSTRIAL STRENGTH HEAVY DUTY DEGREASER

Super concentrated, high alkaline, butyl-based liquid degreaser. A perfectly balanced cleaning degreaser. Superior solvency. Superior detergency. Formulated to work where others fail.

#### ADVANTAGES

- Quickly removes heavy accumulations of grease, oil, and dirt. Does not harm fine machine parts
- Reduces cleaning time. Makes tough cleaning jobs easier.
- Highly concentrated — 1 part Enviroway All Purpose Heavy Duty Degreaser with 64 parts water is still an effective cleaner for steam cleaning, floor scrubbing, and light spray cleaning.
- Completely water soluble. Rinses quickly.
- No phosphates. Non flammable.

#### DIRECTIONS

Quickly removes heavy accumulations of grease, oil, dirt. Effective on rubber scuff marks, marking pen ink, crayons, etc. Apply by spraying, wiping, brushing or dipping. Also for use in mop buckets, auto scrubbers and pressure washers.

##### DILUTION TABLE

Light Soil	1:64	( 2 oz. per gallon of water)
Medium Soil	1:32	( 4 oz. per gallon of water)
Heavy Soil	1:10	(13 oz. per gallon of water)
Extreme Soil	1: 5	(26 oz. per gallon of water)

Motors, machinery, trucks, whitewall tires, concrete, ovens, hoods, fans . . . . . 1 to 5

Walls, floors, cabinets, boats, appliances, vinyl leatherette, carpet and upholstery spotting, woodwork, porcelain, plastic and ceramic tile, patio furniture, barbecue utensils, painted aluminum siding . . . . . 1 to 10

Wax stripping, linoleum, asphalt, tile floors, rubber, cork, terrazzo . . . . . 1 to 5

Steam cleaning, floor scrubbing, pressure washing . . . . . 1 to 64

Cannot be used on all surfaces that can be washed with water. If you are in doubt, try on a small area in an inconspicuous spot before proceeding. Undiluted may remove paint, varnish, etch aluminum, magnesium and brass. Do not allow to dry on glass.

#### SPECIFICATIONS

**Physical Form**  
Clear Liquid

**Color**  
Yellow

**Scent**  
Glycol Ether

**Specific Gravity**  
1.070

**Density**  
8.90 lbs. per gallon

**Foam Test 1% Solution**  
Initial - 115 mm  
5 minutes - 70 mm

**pH 2% Solution**  
11.4

**Active Alkalinity**  
3.67%

**Total Alkalinity**  
3.83%

**Total Solids**  
15%

**Total Activity**  
25.58%

**WARNING:**  
Harmful in contact with skin.  
Causes serious eye damage.  
Harmful if swallowed.  
Keep out of reach of children.

**ENVIROWAY PRODUCTS**  
PO Box 68654  
Grand Rapids, MI 49516  
616-272-4188