TECHNICAL DATA SHEET



ENVIROCLEAN ORANGE

PROFESSIONAL GRADE

DEGREASER

Natural citrus water-based degreaser and deodorizer concentrate loosens grease and grime for fast, easy removal. This multi-purpose cleaner strips grease and heavy deposits from virtually any surface. Fresh citrus scent.

ADVANTAGES

- Non-corrosive, Non-flammable, contains no petroleum distillates.
- The safe answer to those tough degreasing, cleaning, and odor control problems.
- Powerful, multi purpose. Used to:
 - * Degrease trucks and heavy equipment
 - * Clean engine and parts
 - Remove tar and asphalt
- · Leaves a fresh citrus scent

DIRECTIONS

All Purpose Degreasing: Quickly penetrates and emulsifies petroleum and food-based greases. Effective on rubber scuff marks, marking pen ink, crayons, etc. Apply by spraying, wiping, brushing, or dipping. Also for use in mop buckets, auto scrubbers, parts washers, and pressure washers.

Light Soil: 1:40 (3 oz. per gallon of water)
Medium Soil: 1:20 (6 oz. per gallon of water)
Heavy Soil: 1:10 (13 oz. per gallon of water)

Engine Degreasing, Parts Cleaner: Dilute 1 part degreaser to 4 parts water. Brush or spray onto surface to be cleaned. Allow to stand for 3-5 minutes for deep penetration. Rinse thoroughly with clear water.

Tar & Asphalt Removal (Light Soil): Apply undiluted to soiled surface by spraying or mopping. Agitate with brush if necessary until soil is emulsified. Rinse thoroughly with clear water. Do not allow degreaser to dry on surface.

Pressure Washing — Trucks & Heavy Equipment: Dilute 1 part degreaser 20 parts water. Spray solution on surface to be cleaned or degreased. Agitate heavily soiled areas with brush if necessary. Rinse with clear water. Do not allow degreaser to dry on surface. DO NOT USE ON GLASS.

Parts Washers: Dilute 1 part degreaser to 20 parts water. Run solution over part and agitate with brush until soil is removed. Rinse part and air dry.

SPECIFICATIONS

Physical Form Free Flowing Liquid

Color Orange

Scent Citrus

Specific Gravity 1.00 ± .05

Density 8.62 lbs. per gallon

Foam Test (1% Solution) Initial - 55 mm

pH Conc. 12.0 ± .5

Total Solids 8.0 ± .5

Total Solvent 5.0 ± .1

WARNING:

Causes serious eye irritation.
Causes skin irritation.
May be harmful if swallowed.

Keep out of reach of children.

ENVIROWAY PRODUCTS

PO Box 68654 Grand Rapids, MI 49516 616-272-4188